

Compact Drive System

Panels > 23 1/8"



Part of the Railtech Architectural Group

TYPICAL DIMENSIONS (Imperial)

Finished Ceiling "A"	Beam Height "B"	Acoustic Barrier "C"	Pocket Depth "D"	Pocket Width "E"	Panel Height "F"	Number of Panels High	Wall Thickness
21'-0"	25'-5"	24'-1"	37"	57 1/2"	23 3/8"	12 Panels Special	11 3/4"
21'-6"	25'-11"	24'-7"	37"	58 1/2"	23 7/8"		11 3/4"
22'-0"	26'-5"	25'-1"	37"	59 1/2"	24 3/8"		11 3/4"
22'-6"	26'-11"	25'-7"	37"	60 1/2"	24 7/8"		11 3/4"
23'-0"	27'-5"	26'-1"	37"	61 1/2"	25 3/8"		11 3/4"
23'-6"	27'-11"	26'-7"	37"	62 1/2"	25 7/8"		11 3/4"
24'-0"	28'-5"	27'-1"	37"	63 1/2"	26 3/8"		11 3/4"
24'-2"	28'-6 1/2"	27'-2 1/2"	36 1/2"	63 3/4"	26 1/2"		11 3/4"

Maximum panel length of 10'-0" for walls > 24'-2" high

24'-6"	29'-6"	27'-11"	42"	61 3/4"	25"	13 Panels High	11 3/4"
25'-0"	30'-0"	28'-5 1/2"	42 1/2"	62 3/4"	25 1/2"		11 3/4"
25'-6"	30'-6"	29'-0"	43"	63 3/4"	26"		11 3/4"
26'-0"	31'-0 1/2"	29'-6 1/2"	43 1/2"	64 3/4"	26 1/2"		11 3/4"
26'-6"	31'-6"	30'-1 1/4"	43 1/4"	62"	25 1/8"	14 Panels High	11 3/4"
27'-0"	32'-0"	30'-6 1/2"	42 1/2"	62 3/4"	25 1/2"		11 3/4"
27'-6"	32'-6"	31'-1 1/2"	43 1/2"	63 3/4"	26"		11 3/4"
28'-0"	33'-0"	31'-6 3/4"	42 3/4"	64 1/2"	26 3/8"		11 3/4"
28'-6"	34'-0"	32'-5 3/4"	48 3/4"	62 1/4"	25 1/4"	15 Panels High	11 3/4"
29'-0"	34'-6"	32'-11 3/8"	48 3/8"	63"	25 5/8"		11 3/4"
29'-6"	35'-0"	33'-5"	48"	63 3/4"	26"		11 3/4"
30'-0"	35'-6 1/2"	34'-0 1/2"	49 1/2"	64 3/4"	26 1/2"		11 3/4"

Note: The information included in this chart is intended as a guide. In all cases Skyfold® shop drawings specific to each project are to be referred to for final build to dimensions. Beam heights can vary pending on can vary depending on motor size